



DISSODATORE PER  
TRATTORI

SUBSOILER FOR  
TRACTORS



DG 50/160 HP (36/118 KW)  
DH 80/320 HP (59/235 KW)



DG 125 >130 cm  
DH 150 >400 cm

DG  
DH



CE

Ideale per lavorare il terreno in profondità,  
favorendone il drenaggio e l'aerazione.

*Ideal to process the soil deeply, thus supporting  
drainage and aeration.*



# DG



## PER TRATTORI DA 50 A 160 HP (36/118 KW)

Attacco 3 punti di II cat. • Ancore in acciaio con bullone di sicurezza • Puntali anti-usura con montaggio rapido • Ancore modulari spostabili • Versione con o senza rullo.

OPTIONAL: Kit protezione anti-usura ancore • Kit esplosore • Bandinelle contenimento zolle • Regolazione rullo idraulica • Kit impianto luci con segnaletica posteriore.



## FOR TRACTORS FROM 50 TO 160 HP (36/118 KW)

2nd cat. 3-point attachment • Steel shanks with safety bolt • Anti-wear tips with fast mounting • Movable modular shanks • Version with / without roller.

OPTIONALS: Shanks wear protection kit • Clod-shattering fins kit • Clod containment sides • Hydraulic adjustment of roller • Light system kit with rear signs.



Modello Model	Larghezza di lavoro Working width	Profondità di lavoro Working depth	Nr. ancore Nr. tines	HP (KW)	KG Peso Weight	KG Peso con rulli Weight with roller
DG 125	125 cm	55 cm	3	50/110 (36/81)	440 kg	800 kg
DG 150	150 cm	55 cm	3	60/110 (44/81)	480 kg	850 kg
DG 175	175 cm	55 cm	5	70/130 (51/96)	630 kg	950 kg
DG 200	200 cm	55 cm	5	70/130 (51/96)	670 kg	1100 kg
DG 225	225 cm	55 cm	5	70/130 (51/96)	710 kg	1150 kg
DG 250	250 cm	55 cm	5	70/130 (51/96)	750 kg	1200 kg
DG 275	275 cm	55 cm	7	100/160 (74/118)	900 kg	1400 kg
DG 300	300 cm	55 cm	7	100/160 (74/118)	950 kg	1450 kg

# DH



## PER TRATTORI DA 80 A 320 HP (59/235 KW)

Attacco 3 punti di II e III cat. • Ancore in acciaio con bullone di sicurezza • Puntali anti-usura con montaggio rapido • Telaio con tubi strutturali rinforzati • Ancore modulari spostabili • Versione con o senza rullo.

OPTIONAL: Kit protezione anti-usura ancore • Kit esplosore • Bandinelle contenimento zolle ripiegabili per trasporto • Regolazione rullo idraulica • Kit impianto luci con segnaletica posteriore.



## FOR TRACTORS FROM 80 TO 320 HP (59/235 KW)

2nd and 3rd cat. 3-point attachment • Steel shanks with safety bolt • Anti-wear tips with fast mounting • Frame with strengthened structural tubes • Movable modular shanks • Version with / without roller.

OPTIONALS: Shanks wear protection kit • Clod-shattering fins kit • Clod containment sides that can be folded for transport • Hydraulic adjustment of roller • Light system kit with rear signs.



Modello Model	Larghezza di lavoro Working width	Profondità di lavoro Working depth	Nr. ancore Nr. tines	HP (KW)	KG Peso Weight	KG Peso con rulli Weight with roller
DH 150	150 cm	60 cm	3	80/180 (59/132)	750 kg	1100 kg
DH 200	200 cm	60 cm	5	90/220 (66/162)	1000 kg	1400 kg
DH 250	250 cm	60 cm	5	110/250 (81/184)	1150 kg	1600 kg
DH 300	300 cm	60 cm	7	130/280 (96/206)	1400 kg	1900 kg
DH 350	350 cm	60 cm	9	170/300 (125/221)	1600 kg	2200 kg
DH400	400 cm	60 cm	9	190/320 (140/235)	1750 kg	2400 kg



FOLLOW US



ORTOLAN ANDREA macchine agricole | Via Lungochiampo, 90 | MONTEBELLO (VI) | ITALY  
Tel. e Fax +39 0444 440960 | info@ortolanandrea.it | www.ortolanandrea.it